

## THE AQUA JET II - WASHDOWN PUMPS AND KITS

Johnson Pump Marine's new Aqua Jet II Washdown Pump is built to excel in harsh saltwater environments. This next-generation pump delivers powerful performance, smooth operation, and unmatched corrosion resistance with the flexibility today's boaters demand.

### Built to Last

Engineered with a dual-layer surface treatment, E-coating followed by powder coating, Aqua Jet II is designed to withstand the toughest marine conditions. Its compact flexible bracket design allows versatile installation, while KlickTite enable tool-free inspection or assembly. The proven 5-chamber diaphragm system ensures reliable flow and quiet, efficient operation.

### Common Applications:

Perfect for rugged marine use, Aqua Jet II pumps are ideal for:

- Deck and surface washdowns: bait and fish stations, cockpit, anchor, and transom clean-up
- Regulatory cleaning: supporting invasive species decontamination standards for trailered boats



**QUICK-CHANGE ELECTRICAL CONNECTION**



**SIMPLIFIED PUMP MOUNTING BRACKET**



| FEATURES                    | BENEFITS/ADVANTAGES                                                                                        |
|-----------------------------|------------------------------------------------------------------------------------------------------------|
| 5 Chamber Membrane Design   | Self priming up to 2.5m and can run dry<br>Quiet and pulsation-free operation compared to less chambers    |
| Quick-Change Connection     | Included harness connection requiring no cutting and splicing of wires                                     |
| Pressure Switch             | Automatic operation                                                                                        |
| KlickTite Port Connection   | Easy installation and maintenance                                                                          |
| Corrosion-Resistant Design  | Withstands harsh conditions thanks to e-coating and powder coating                                         |
| Dry-Running Ability         | Reliable performance even if water levels are low                                                          |
| Thermal Overload Protection | Protection against overheat, extending pump life                                                           |
| High Torque & Rpm Motor     | High pressure - 5 bar                                                                                      |
| Nitrile Rubber Membrane     | Withstands raw water                                                                                       |
| Warranty                    | 3-Years                                                                                                    |
| PC-ABS Plastic Bracket      | Removable pump for easy installation, maintenance, and winterization allowing for easy pump rotation       |
| Inlet Strainer              | Built-in KlickTite for easy inlet installation<br>Protect the pump from debris and extend its service life |

**AQUA JET II FULL KIT**



**AQUA JET II HALF KIT**





## TECHNICAL SPECIFICATIONS

|                         | PART NUMBER | DESCRIPTION            | CAPACITY           | PRESSURE CUT OFF | FUSE SIZE | MOTOR | LENGTH | WIDTH  | HEIGHT | WEIGHT |
|-------------------------|-------------|------------------------|--------------------|------------------|-----------|-------|--------|--------|--------|--------|
| <b>REPLACEMENT PUMP</b> | 10-25013-13 | AQUA JET II WD 3.5 12V | 13 l/min (3.5 GPM) | 5 bar            | 20 A      | 120W  | 218 mm | 201 mm | 116 mm | 2.4 kg |
|                         | 10-25014-13 | AQUA JET II WD 5.2 12V | 20 l/min (5.2 GPM) | 5 bar            | 20 A      | 185W  | 222 mm | 209 mm | 112 mm | 2.5 kg |
|                         | 10-25014-14 | AQUA JET II WD 5.2 24V | 20 l/min (5.2 GPM) | 5 bar            | 10 A      | 185W  | 222 mm | 209 mm | 112 mm | 2.5 kg |
| <b>HALF KIT</b>         | 10-25013-03 | AQUA JET II WD 3.5 12V | 13 l/min (3.5 GPM) | 5 bar            | 20 A      | 120W  | 218 mm | 201 mm | 116 mm | 2.4 kg |
|                         | 10-25013-04 | AQUA JET II WD 3.5 24V | 13 l/min (3.5 GPM) | 5 bar            | 10 A      | 120W  | 218 mm | 201 mm | 116 mm | 2.4 kg |
|                         | 10-25014-03 | AQUA JET WD 5.2 12V    | 20 l/min (5.2 GPM) | 5 bar            | 20 A      | 185W  | 222 mm | 209 mm | 112 mm | 2.5 kg |
|                         | 10-25014-04 | AQUA JET II WD 5.2 24V | 20 l/min (5.2 GPM) | 5 bar            | 10 A      | 185W  | 222 mm | 209 mm | 112 mm | 2.5 kg |
| <b>FULL PUMP KIT</b>    | 10-25013-14 | AQUA JET II WD 3.5 12V | 13 l/min (3.5 GPM) | 5 bar            | 20 A      | 120W  | 218 mm | 201 mm | 116 mm | 2.4 kg |
|                         | 10-25014-15 | AQUA JET II WD 5.2 12V | 20 l/min (5.2 GPM) | 5 bar            | 20 A      | 185W  | 222 mm | 209 mm | 112 mm | 2.5 kg |
|                         | 10-25014-16 | AQUA JET II WD 5.2 24V | 20 l/min (5.2 GPM) | 5 bar            | 10 A      | 185W  | 222 mm | 209 mm | 112 mm | 2.5 kg |

|                              |                                                                                                                                                   |
|------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Diaphragm</b>             | Santoprene                                                                                                                                        |
| <b>Valves</b>                | Nitrile                                                                                                                                           |
| <b>Body</b>                  | PP/PPA                                                                                                                                            |
| <b>Bracket</b>               | PC-ABS                                                                                                                                            |
| <b>Hole Pattern:</b>         | Width: 108 mm   Length: 63.5 mm   Ø 5.2 mm                                                                                                        |
| <b>Replacement pump:</b>     | Pump with Filter                                                                                                                                  |
| <b>Half Kit:</b>             | Pump with inlet strainer, pistol and two different connectors for the pistol (Garden Hose Threaded or Quick Grip Connector)                       |
| <b>Full Kit:</b>             | Pump, inlet strainer, spray pistol, Klicktite barb port fittings, bulkhead fitting, 7.5m coiled hose & threaded connector for the pistol and coil |
| <b>KlickTite Connection:</b> | 2 Pcs of 3/8" BSP & 1/2" Hose Barb / 2 Pcs of 1/2" NPT & 3/4" Hose Barb / 1 Pcs of 3/4" Garden Hose Thread                                        |

